Product data sheet


INFINITE PRO 1700MM RECESSED OPTICELL
AK19-48W8CLOS14
LEDSC4



IP 40

LedsC4 Infinite Pro 1700mm Recessed Opticell AK19-48W8CLOS14 Lineal lighting system for indoor use. For downlighting. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 3.42 Product length (mm): 1700 Product width or diameter (mm): 75 Product height (mm): 82 Ø of the hole for recessing (mm): 1705x65 Permitted ceiling thickness: 0-25 Class 1. Luminaire not suitable for coating with insulation materials. IP: IN IP20 / OUT IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: PHILIPS. Maximum power of light source: 44W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 17.9. Photobiological risk: RG1. % de Flickering: <4%. Real flux (lm): 7371. Real lm/W: 151. Voltage / frequency range: 220-240V/50-60Hz. Voltage: 240. Equipment included: Yes. Total power: 48.9. Power factor: 0.95. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	48.93 W	LOR	100%
Lamp flux	7371 lm	Total flux	7370 lm
Luminous efficacy	151 lm/W	Total power	48.93 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 66.93 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 48.93 W
Appliance Class: I

Protection

IP: 40