Product data sheet


INDUSTRIAL AND WAREHOUSE LIGHTING
V1-I0-70580-03000-6708040 IRON GL 1,5 M 80W 4000K TEMPERED GLASS LAMBERT
VARTON



IP 67 IK 08

Linear lamp in an anodized aluminum housing for fire-hazardous areas with low ceilings, impact-resistant tempered glass, a wide range of lengths and capacities. The CLEANPRO version is a dirt-repellent (oleophobic) coating on the glass. Installation: Suspended (cable suspension is ordered separately) and overhead, using stainless steel brackets (included in the delivery package). The suspensions snap into a groove located along the entire length of the lamp, which allows you to adjust the position of the already mounted lamp. Application: Lighting of rooms with low ceilings - industrial premises, food industry workshops, livestock complexes, clean rooms, industrial workshops, warehouses, transport infrastructure, fire-hazardous areas Power factor: 0,95 Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Input voltage (DC), V: 190...280 Flicker, %: 5 Climatic modification and category of placement: УХЛ1 Protection class: I Ingress protection (IP): IP67 Impact resistance: IK08 https://www.varton.ru/products/promyshlennoe-i-skladskoe-osveshchenie/iron-gl/iron-gl-1-5-m/svetodiodnyy-svetilnik-varton-ayron-gl-80-vt-4000-k-1465kh86kh76-mm-klass-zashchity-ip67-rasseivatel/

Light output 1



1 x LED

Nominal lamp power	80 W	LOR	100%
Lamp flux	11080 lm	Total flux	11081 lm
Luminous efficacy	138 lm/W	Total power	80 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.68 in
Width: 3.39 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 80 W

Protection

IP: 67
IK: 08