Product data sheet


AME LED NM3
AME EMERGENCY
DEXTRA



IP 65 IK 07 CE

AME LED - IP65, IK07. Non-maintained 3hr emergency luminaire, robust polycarbonate body and lens, white finish with clear reeded diffuser. 175 lumens emergency output. Options: ST3 - Self Test Module (7 Watts Rated Power) (250 lumens maintained mode, 150 lumens in non-maintained mode) AT3 - Self Test Module (6 Watts Rated Power) CB - Please specify 50v, 110v or 230v when ordering AME ELK - Emergency Legend Kit AME ELK ISO - Emergency Legend kit ISO 7010

Light output 1 (emergency)



1 x LED

Nominal lamp power	1 W	LOR	88%
Lamp flux	150 lm	Total flux	131 lm
Luminous efficacy	150 lm/W	Total power	2.4 W
CCT	4000 K		
CRI	99		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 13.86 in
Width: 4.33 in
Height: 2.56 in

Adjustability

Fixed

Electric

System power: 2.4 W
Ballast: ECG

Information regarding emergency functions

Emergency lighting only
Emergency power supply: Single battery 3 h
Emergency sign: N/A

Protection

IP: 65
IK: 07
Designation labels: CE