

Product data sheet

LED DOWNLIGHTS
V1-R0-91808-10D01-5401230 12W 3000K DALI
VARTON




IP
54

IK
01

Input voltage (AC, 50Hz), V: 198...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Protection class: II Housing material: Steel Mounting method: Built-in Ingress protection (IP): IP54 Impact resistance: IK01 Power factor: 0,95 https://www.varton.ru/products/daunlayty/dl-grill/dl-grill-ip54-cri90-yacheyka-100kh100-mm-shirina-lameli-10-mm/svetodiodnyy-svetilnik-varton-dl-grill-100kh100-mm-12-vt-cri90-dlya-potolka-grilyato-s-shirinoy-lame_22/

Light output 1



1 x LED			
Nominal lamp power	12 W	LOR	100%
Lamp flux	950 lm	Total flux	950 lm
Luminous efficacy	79 lm/W	Total power	12 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.54 in
Width: 3.54 in
Height: 6.30 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 54
IK: 01