


Product data sheet


ALEA SPOT
641317.002.76
RZB



IP
20

Series: Alea Spot Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Pole: aluminium. Cover: plastic sphere, opal, satin finish. "Triple lamp; mains connection through pole to terminal in" "pole top; base plate: D 300. 4 mounting holes: D 10; pitch" circle for holes: D 230. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 306, B 75, H 2 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 950lm System power: 8,2W Beam Angle: 60°/58° Number of fittings B10A: 82 Number of fittings B16A: 130 Inrush current: 5A Unified Glare Ratio: 16,7 EEC: A+

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 8.2 W | CRI | 80 |
| Total flux | 950 lm | LOR | 100% |
| Luminous efficacy | 116 lm/W | Total power | 8.2 W |

Mounting mode

Wall recessed

Shape and measurements

Length: 2.95 in
Width: 12.05 in
Height: 1.46 in

Adjustability

Fixed

Electric

System power: 8.2 W

Protection

IP: 20