Product data sheet

METRO PRO BLACK 2X 2010LM 3000K RA>70 ON/OFF
7021986117974
SG ARMATUREN



IP 66 IK 07

Metro Pro is a solid outdoor luminaire for decorative and functional lighting of facades and city spaces. Available in two versions: up- and downlight or just downlight. The downlight gives a wide and powerful light. The uplight is a decorative light beam that gives a nice touch to the façade. Easy installation with loopable screwless terminal blocks and wall fitting with quick connector to lamp. Option of either visible or concealed cabling. Light distribution Direct/Indirect Light technic LED 28W 3000K Ra>70 SDCM 5 L90/B10>50,000 hrs Protection Class I IP66 IK07 Materials and finish Housing: Aluminium Colour: Black Optics: Tempered glass Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light output 1



1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	2010 lm	ULOR	15%
Luminous efficacy	72 lm/W	Total flux	2009 lm
CCT	3000 K	Total power	28 W
CRI	70		

Mounting mode

Wall mounted

Shape and measurements

Length: 4.72 in
Width: 8.27 in
Height: 11.65 in

Adjustability

Fixed

Electric

System power: 28 W
Appliance Class: I

Protection

IP: 66
IK: 07