

Product data sheet

ELLIS2 - 20W - 1950LM - FLOOD 29°
0478001A-840
ARCLUCE




IP
65

IK
07

IP DEGREE : IP65 IK RATING : IK07 ELECTRICAL INSULATION CLASS: I LUMINAIRE Extruded aluminium body. Die-cast aluminium trim (EN 47100). Double layer polyester powder paint resistant to corrosion and salt spray fog. Silicone rubber gaskets. AISI 316 stainless steel external screws. PMMA lenses for LEDs. Screen made of 10mm thermal-shock resistant tempered glass. High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80. It complies with standards EN 60598-1 and EN 60598-2-1. INSTALLATION Wall mounted. Tecnopolymer M20 cable gland. For bidirectional versions, wiring in double switch.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	1950 lm	LOR	100%
Luminous efficacy	98 lm/W	Total power	20 W

Mounting mode

Wall mounted

Shape and measurements

Length: 7.87 in
Width: 8.27 in
Height: 11.22 in

Adjustability

Rotatable

Electric

System power: 20 W

Protection

IP: 65
IK: 07