

Product data sheet


PTECD L11 LE3 & PTECD R *
 PROTEC LED EMERGENCY
 DEXTRA



IP
20


Protec LED - Ø174mm, IP20 Recessed downlighter with ABS housing and bezel, zinc plated spring steel fixing clips, anodised aluminium reflectors. LE3 - Lithium Emergency LS3 - Lithium Selftest LA3 - Lithium Autotest Emergency Lumen Values: No Coloured Ring: Opti-Spec: 367, Opti-Sat: 357 Drop Glass Ring: Opti-Spec: 344, Opti-Sat: 335 IP44 Cover: Opti-Spec: 343, Opti-Sat: 333 Microprism Diffuser: Opti-Spec: 274, Opti-Sat: 263 Opal Diffuser: Opti-Spec: 262, Opti-Sat: 243 S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* Replace * with WH for white ring or GY for Grey

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	8.9 W	CRI	80
Total flux	1042 lm	LOR	100%
Luminous efficacy	117 lm/W	Total power	8.9 W

Light output 2 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	405 lm	LOR	100%
Luminous efficacy	101 lm/W	Total power	4 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.57 in

Diameter: 6.85 in

Adjustability

Fixed

Electric

System power: 12.9 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20