Product data sheet


PML WITH BRACKET MADRID 600-2 DOUBLE M5 16LED 4000K
88.05700.0VXXX + 10.35701.2V001
HESS



IP 54


Round luminaire canopy made of aluminium, plain coloured. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium. 10.35701.2V001 PARALLEL Bracket MADRID 600/600-2/800-2 double Made of galvanised steel Overhanging 450 mm on each side Spigot pole ø 76,1 mm

Light output 1




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	2133 lm	Total flux	2133 lm
Luminous efficacy	136 lm/W	Total power	15.7 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1762 lm	Total flux	1762 lm
Luminous efficacy	131 lm/W	Total power	13.4 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1377 lm	Total flux	1377 lm
Luminous efficacy	124 lm/W	Total power	11.1 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2850 lm	Total flux	2850 lm
Luminous efficacy	141 lm/W	Total power	20.2 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	3193 lm	Total flux	3193 lm
Luminous efficacy	142 lm/W	Total power	22.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2497 lm	Total flux	2497 lm
Luminous efficacy	139 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4821 lm	Total flux	4821 lm
Luminous efficacy	142 lm/W	Total power	33.9 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4506 lm	Total flux	4506 lm
Luminous efficacy	143 lm/W	Total power	31.6 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	4189 lm	Total flux	4189 lm
Luminous efficacy	142 lm/W	Total power	29.4 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3864 lm	Total flux	3864 lm
Luminous efficacy	143 lm/W	Total power	27.1 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3532 lm	Total flux	3532 lm
Luminous efficacy	142 lm/W	Total power	24.8 W
CCT	4000 K		
CRI	80		

Light output 2




1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	3864 lm	Total flux	3864 lm
Luminous efficacy	143 lm/W	Total power	27.1 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	3193 lm	Total flux	3193 lm
Luminous efficacy	142 lm/W	Total power	22.5 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2850 lm	Total flux	2850 lm
Luminous efficacy	141 lm/W	Total power	20.2 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2497 lm	Total flux	2497 lm
Luminous efficacy	139 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	2133 lm	Total flux	2133 lm
Luminous efficacy	136 lm/W	Total power	15.7 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1762 lm	Total flux	1762 lm
Luminous efficacy	131 lm/W	Total power	13.4 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1377 lm	Total flux	1377 lm
Luminous efficacy	124 lm/W	Total power	11.1 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	4189 lm	Total flux	4189 lm
Luminous efficacy	142 lm/W	Total power	29.4 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	3532 lm	Total flux	3532 lm
Luminous efficacy	142 lm/W	Total power	24.8 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	4821 lm	Total flux	4821 lm
Luminous efficacy	142 lm/W	Total power	33.9 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	4506 lm	Total flux	4506 lm
Luminous efficacy	143 lm/W	Total power	31.6 W
CCT	4000 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 38.43 in
Width: 3.74 in
Height: 12.91 in

Adjustability

Fixed

Electric

System power: 22.2-67.8 W

Protection

IP: 54