


Product data sheet

DIAMO MD 1000-927 SWI WW-DWH WH
60210956
ZUMTOBEL



Miniaturised LED light module (wallwasher); compact construction and purist appearance; asymmetric light distribution with optimised lighting technology for illuminating vertical surfaces; lamp(s): 1/18W LED1000-927; Colour rendering Ra > 90, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 998 lm, Luminaire efficacy: 55 lm/W; service life: 50000h for luminous flux at 80% of initial value; with control unit, switchable luminaire; as multifunctional lamp unit rotatable (180°) in combination with DIAMO Gimbal installation frame with trim or plaster surround (trimless); innovative thermal design achieves passive cooling; housing made of die-cast aluminium, white; reflector: high-grade aluminium, silver anodised; luminaire wired with halogen-free leads; power connection: 2-pole terminal; total power: 18 W; mains voltage: 220-240V/ 0/50/60Hz ; simple, tool-free mounting of modules in installation frame (Gimbal) via CLIX technology; Dimensions: Ø65 x 89 mm, weight: 0.42 kg; Note: Various colour combinations (design personalisations) of single components possible due to modular construction, and orderable as variant via myDIAMO: Note: The DIAMO Gimbal installation frame (single, double or triple) must be ordered separately.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	90
Total flux	1000 lm	LOR	100%
Luminous efficacy	56 lm/W	Total power	18 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.50 in
Diameter: 2.56 in
Weight: 0.421 kg

Design

Material impression: Aluminum
Color of housing: White

Electric

System power: 18 W
Voltage: 220-240 V AC
Appliance Class: II

Protection

IP: 20
Designation labels: CE