


# Product data sheet

LP SLIM BOX SURFACE MOUNTED BLACK LED 3000K 25W PRISM  
91794-1006  
LOUIS POULSEN



LP Slim Box Surface Mounted Design: Louis Poulsen A/S Concept: The product family shares a high-efficiency light unit framed in a rectangular housing. The recessed variants emit downwardly directed light, while the suspended and surface-mounted variants provide a combination of primarily downwardly directed and indirect light. Choosing between opal diffusers or micro-prismatic solutions, the glare and visual expression can be balanced as desired. The light egress emphasizes the design detail in the housing, ensuring a comfortable and subtle yet distinct design. Finish: White or black, powder coated or clear lacquered, pickled aluminium. Materials: Frame/Housing: Die cast Aluminium Light Engine bottom: Acrylic (Opal or clear) Light Engine top: Acrylic opal Mounting: Directly on ceiling or wall. Looping: Approved, max. 5 x 1.5 mm². Integrated driver. Cable entries: Rear, side-mounted. Integrated driver. It can be positioned both vertically and horizontally for wall-mounting. Sizes and weights: Width x Height x Length (mm) 689 x 805 x 150 Max 4.1 kg Class: Ingress protection IP20. Electric shock protection I.

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 25 W    | CRI         | 90     |
| Total flux         | 2295 lm | LOR         | 69%    |
| Luminous efficacy  | 92 lm/W | Total power | 25 W   |

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 27.17 in

Width: 5.91 in

Height: 3.19 in

## Adjustability

Fixed

## Electric

System power: 25 W

Appliance Class: I

## Protection

IP: 20