


# Product data sheet

SCON-S AC 250 LED650-930 LDO SP BZ  
60510299  
ZUMTOBEL



Spherical pendant luminaire; sphere of polycarbonate with semi-transparent, reflective bronze-plated finish; lighting impact: semi-transparent reflection of light creates sense of plasticity and depth; lamp(s): LED650-930, Luminaire or spotlight with SPOT light distribution (17 °); Colour rendering Ra > 90, colour temperature 3000 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 650 lm, Luminaire efficacy: 72 lm/W; service life: 50000h for luminous flux at 80% of initial value; UV-free and IR-free light; modular, high quality optical unit consisting of reflector and LED light chamber; passive thermal management achieved by optimised design of luminaire housing; reflector made of high-quality, UV-resistant polycarbonate, highly reflective aluminized finish, iridescence-free; electronic control gear Slave luminaire for DALI control (DALI only), integrated in ceiling rose; ceiling rose of polycarbonate, chrome matt; transparent pendant cord; electrical connection: 5-pole connector terminal; total power: 9 W; mains voltage: 220-240V/ 50/60Hz ; class of protection: I; Dimensions: Ø250 mm, total length approx. 3000mm; weight: 1.2 kg

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 9 W     | CRI         | 90     |
| Total flux         | 650 lm  | LOR         | 100%   |
| Luminous efficacy  | 72 lm/W | Total power | 9 W    |

## Mounting mode

Pendant

## Shape and measurements

Height: 9.84 in  
Diameter: 9.84 in  
Weight: 1.2 kg

## Design

Material impression: Plastic

## Electric

System power: 9 W  
Voltage: 220-240 V AC  
Controller: DALI  
Appliance Class: I

## Protection

IP: 20  
Designation labels: CE