
Product data sheet

LUCAS X (WALL FITTING BEADED) 9.833.2056.16 LEIPZIGER LEUCHTEN

Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



| 1 x High | pressure | sodium | vapour | lamp |
|----------|----------|--------|--------|------|

IP 55

| Nominal lamp power | 100 W | LOR | 83% | | |
|--------------------|----------|-------------|---------|--|--|
| Lamp flux | 10400 lm | ULOR | 2% | | |
| Luminous efficacy | 75 lm/W | Total flux | 8621 lm | | |
| CCT | 2000 K | Total power | 115 W | | |
| CRI | 25 | | | | |
| | | | | | |



| 1 x High | pressure sodium | vapour | lamp |
|----------|-----------------|--------|------|

| Nominal lamp power | 70 W | LOR | 83% |
|--------------------|---------|-------------|---------|
| Lamp flux | 5600 lm | ULOR | 2% |
| Luminous efficacy | 56 lm/W | Total flux | 4642 lm |
| ССТ | 2000 K | Total power | 83 W |
| CRI | 25 | | |
| | | | |

Mounting mode Wall mounted Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Electric

System power: 83-115 W

Protection

IP: 55