
Product data sheet

GALAXY_CVR_SYSTEM_TWO_WAY_D1505MM_45D_9W+9W_NEUTRAL
820922123_
PETRIDIS



GALAXY CVR / GALAXY CVR-D is a 24V DC low voltage aluminium profile. It is an ideal solution for small showcases, homes, rest areas, museums, hotels, exhibition halls and generally for many decorative and architectural projects. Technical Features - Aluminium body, painted electrostatically in selected colour. - Connection for operation with 24V DC. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). Upon Request - Available also in 2700 Kelvin CRI 90. ---------- Details for Dialux: D805 - 8pcs R 0.375m D1205 - 8pcs R 0.575m D1505 - 8pcs R 0.725

Light output 1



1 x LED

Nominal lamp power	18 W	LOR	57%
Lamp flux	2511 lm	Total flux	1421 lm
Luminous efficacy	140 lm/W	Total power	18 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Length: 22.68 in
Width: 3.27 in
Height: 2.17 in

Adjustability

Fixed

Design

Material impression: Aluminum, Chrome, Plastic

Electric

System power: 18 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: III

Protection

IP: 40
Designation labels: CE