# Product data sheet

HANCE G2 TRACK 220 3000 NW FL DALI BK
HS2TK30FL840DB
LAMP



IP 20 IK 07

LAMP three-phase track multidirectional spotlight HANCE G2 TRACK 2203000 . Allowing 355º rotation and tilting up to 90º. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35º flood reflector. LED COB, 4000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25ºC). Available finishes: Textured white and textured black.

## Light output 1



### 1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 27.5 W | LOR | 100% |
| Lamp flux | 3318 lm | Total flux | 3312 lm |
| Luminous efficacy | 121 lm/W | Total power | 27.5 W |
| CCT | 4000 K | | |
| CRI | 80 | | |

### Mounting mode

Ceiling mounted, Contact rail

### Shape and measurements

Height: 8.27 in
Diameter: 3.54 in

### Adjustability

Rotatable, Tiltable

### Electric

System power: 27.5 W
Appliance Class: II

### Protection

IP: 20
IK: 07