Product data sheet

SYSTEM BATTEN LUMINAIRE TRAQ M1200 28W 4250LM CRI > 80 3000K SILVER ON/OFF
2005.5169 - TRAQ INS M1200 LED4250-830 WB SR IP54 ONF


REGENT



IP 54 IK 06

System batten luminaire Traq m1200, for mounting on Traq Linear mounting rail, with LED, system power: 28 W, luminous flux of luminaire 4250 lm, colour rendering index CRI > 80, 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 72'000 h, Photobiological safety: Safe., 230 V, direct light emission gear tray made of aluminium silver similar to RAL 9006 powder coated, with UV-resistant LED optics in polymethyl methacrylate (PMMA), wide beam, 1 integral control gear, ON/OFF, with halogen-free wiring, ENEC certified, support profile and system components to be ordered separately Ingress protection IP54 applies to the complete IP54-compatible system Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0295), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20 / IP54, suitable for mounting on normally inflammable surfaces impact strength: IK 06, for ambient temperatures -10 to +45 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1125953 L = 1186 mm, B = 65 mm, H = 10 mm

Light output 1



1 x LED

Nominal lamp power	33 W	LOR	100%
Lamp flux	4250 lm	ULOR	10%
Luminous efficacy	129 lm/W	Total flux	4251 lm
CCT	3000 K	Total power	28 W
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 46.69 in
Width: 2.56 in
Height: 0.94 in
Weight: 1.78 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 28 W
Appliance Class: I

Protection

IP: 54
IK: 06