Product data sheet

NEOS
7246-E-A-668-XX
UNILAMP



IP 66 IK 08

NEOS NEOS is a small sized high performing area light. Outstanding optical efficacy, high ambient temperature rating and a wide range of mounting accessory makes NEOS a highly competitive product. The smooth curved design eliminates accumulation of water and dust. The unobtrusive slim design is a great match for commercial and residential lighting tasks. The area light can be either equipped with a photocell, DALI-2 control or basic on-off control gear. NEOS can be equipped with mounting accessories for pole integrated mounting, pole bracket, wall and wall corner. The pole bracket is suitable for Pole diameters up to 105mm. Features: • Photocell for simple and cost effective light management • Easy spec: one luminaire part code multiple mounting options • Supreme surge protection: mains and dimming line 10kV protected • Prewired cable 2000mm

Light output 1



1 x LED

Nominal lamp power	23 W	LOR	88%
Lamp flux	4220 lm	Total flux	3706 lm
Luminous efficacy	183 lm/W	Total power	25 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 6.67 in
Width: 4.13 in
Height: 9.29 in

Adjustability

Rotatable, Tiltable

Electric

System power: 25 W
Controller: DALI
Appliance Class: I

Protection

IP: 66
IK: 08