# Product data sheet

DEECOS P MINI
911517.004.3.76_982672.004
RZB



IP 20 IK 06

Series: DEECOS P mini Cylindrical pendant luminaire. Housing made of die-cast aluminium, powder-coated. Canopy made of powder-coated sheet steel, with magnetic attachment. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Best colour rendering index Ra>90. Transparent pendant cable 5 m, can be shortened, with integrated steel cable. High quality converter without flickering and stroboscopic effect. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Suitable for accessory Deecos P Tube cylinder extensions 0.5 m, 0.75 m or 1 m. Colour: silver Diameter: 87 mm Height: 195 mm Suspension length: 5000 mm Lamp: LED Socket: without socket Colour temperature: 3500K Colour rendering index (CRI): 90 System power: 20 W Rated luminous flux: 2250 lm Beam angle Down: 32° Luminous efficiency: 113 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 20 W | CRI | 80 |
| Total flux | 2050 lm | LOR | 67% |
| Luminous efficacy | 102 lm/W | ULOR | 14% |
| | | Total power | 20 W |

### Mounting mode

Pendant

### Shape and measurements

Height: 7.68 in
Diameter: 3.43 in

### Adjustability

Fixed

### Electric

System power: 20 W

### Protection

IP: 20
IK: 06