



Product data sheet

LINEAR LIGHTING
V1-R0-70385-05000-4005030 Q-40 1,2 M 50W 3000K
VARTON



• 40 mm wide luminaire made of extruded aluminum • diffuser with bevelled corners • Adjustable end-cap, allowing to change continuous line direction in 90° increments • External driver in protective case • Unified design with the Q-80 Application • Retail spaces • Offices • Corridors • Hospitality (restaurants, hotels, coffee bars) Installation • Surface-mounted • Suspended (optional) Power factor: 0,95 Input voltage (AC, 50Hz), V: 176...264 AC frequency, Hz: 50 Flicker, %: 1 Climatic modification and category of placement: УХЛ4 Color rendering index: 80-89 Protection class: I Mounting method: Surface mounting/hangable Ingress protection (IP): IP40 Radiation angle, °: 100 Impact resistance: IK01
<https://www.varton.ru/products/lineynye-svetilniki-dlya-vnutrennego-osveshcheniya/q-40/q-40-1-2-m/svetodiodnyy-svetilnik-var-ton-q-40-podvesnoy-nakladnoy-50-vt-1207kh40kh40-mm-3000-k-ip40-s-rasseivat/>

Light output 1



1 x LED			
Nominal lamp power	50 W	LOR	100%
Lamp flux	4900 lm	Total flux	4900 lm
Luminous efficacy	98 lm/W	Total power	50 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Electric

System power: 50 W

Shape and measurements

Length: 47.52 in
Width: 1.57 in
Height: 1.57 in

Protection

IP: 40
IK: 01

Adjustability

Fixed