Product data sheet

POWERMISSION 2 STREET LIGHTING LUMINAIRES PO29-GP015-ME-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	13.3 W	CRI	80
Total flux	1637 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	13.3 W

Mounting mode

Wall mounted, Pole top mounted

Shape and measurements

Length: 18.50 in Width: 12.68 in Height: 5.31 in Weight: 4.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 13.3 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 66 IK: 07

Surface temperature: 40°C