# Product data sheet


GRIFF L
GRIFF-L-SYM02-64LED-3000K-700 MA
RAGNI



IP 66

The Griff range is intended for small or medium height road or residential lighting for the Griff S luminaire and medium and large heights road lighting for the Griff L & XL luminaires. Elongated trapezoidal shaped, it has fins on the top exept for the L version going up to 64 LED. It is entirely made of injected cast aluminum and the dedicated PCB is protected by a screen-printed glass. The Griff XL can receive up to 80 LED. The thermal management of the luminaire is ensured by the module itself, thermally self-managed. Totally IP66, it is fixed laterally on a wall, a mast or a console or at the top of a mast. Griff S is available in 1 or 2 lights, Griff XL in 1 light only.

## Light output 1



### 1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 135.7 W | LOR | 100% |
| Lamp flux | 19345 lm | Total flux | 19345 lm |
| Luminous efficacy | 143 lm/W | Total power | 135.7 W |
| CCT | 3000 K | | |
| CRI | 70 | | |

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 31.50 in
Width: 11.81 in
Height: 3.94 in

## Adjustability

Fixed

## Electric

System power: 135.7 W

## Protection

IP: 66