


Product data sheet


FX35-P1012 0/100 1500 830 OP
GLAMOX



IP
20

Light source LED 1400 - 5600 lumen out Colour temperature 3000/4000 Kelvin, CRI Ra 80, MacAdams 3. Driver Available with constant light (HF) and dimmable (DALI) drivers. Driver life time up to 100.000 h/10 % (max failure) at Ta 25°C. Body material & colour Body in extruded anodized aluminum with end caps in die-casted aluminum. Could also be delivered in white or black. Mounting For pendent or surfaced mounting. Suspension wire and bracket for surfaced mounting has to be ordered separately. See accessories. Accessories Suspension wire and bracket for surfaced mounting has to be ordered separately. Connection Supplied with 2,5m cable Optics Available with Opal diffuser (OP), Microprismatic diffuser (MP) black reflector (BL) and parabolic louvers (SL). Emergency system Available with integrated emergency (1h), Self test (ST) or DALI.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	1400 lm	LOR	100%
Luminous efficacy	117 lm/W	ULOR	84%
		Total power	12 W

Mounting mode

Pendant

Electric

System power: 12 W

Shape and measurements

Length: 39.84 in

Width: 1.38 in

Height: 2.56 in

Protection

IP: 20

Adjustability

Height adjustable