
Product data sheet


INP350LED-0300-OL1-1-35E-30-10PCI-GS-PC-RC
31-550-03OL102
ATM LIGHTING



IP 65 IK 10

Custodial light fixture with LED modules, designed to provide very high shock resistance (IK11+) and to be mounted in the recess in the ceiling or wall of a cell or a corridor. Robust construction and special security screws prevent unauthorized access and eliminate ligature risk. The housing is made of powder coated galvanized steel and the diffuser is made of thick polycarbonate. | Weight: 5.5kg | Ambient temperature range: -20÷50°C

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14.5 W	CRI	80
Total flux	1510 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	14.5 W

Mounting mode

Ceiling recessed, Wall recessed

Shape and measurements

Length: 14.57 in
Width: 14.57 in
Height: 3.54 in

Adjustability

Fixed

Design

Material impression: Gloss
Color of housing: White
Designer: Mirosław Dudak

Electric

System power: 14.5 W
Ballast: ECG
Suitable for feed-through wiring
Appliance Class: I

Protection

IP: 65
IK: 10
Designation labels: CE

Other operating numbers

Ambient temperature range: -4...122°F