Product data sheet

PITTSBURGH 3 FLOODLIGHTS, PROJECTORS AND COLUMN PROJECTORS
PIB-50021-T4B-8040
LIGMAN

IP 66 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Extruded aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Galvanized steel arm mounted - Thermal heat dissipation body - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency polycarbonate lens - Clear toughened glass - Integral control gear - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40.5 W	CRI	80
Total flux	3688 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	100%
		Total power	40.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40.5 W	CRI	80
Total flux	3688 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	100%
		Total power	40.5 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	40.5 W	CRI	80
Total flux	3688 lm	LOR	100%
Luminous efficacy	91 lm/W	ULOR	100%
		Total power	40.5 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 24.88 in
Width: 3.54 in
Height: 20.59 in
Weight: 16 kg

Adjustability

Free

Electric

System power: 121.5 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C