
Product data sheet


RING50MUTE
RG5MH-108301-HXXXM
EGLO



IP 20


pendant mounted direct LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	825 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	6.91 W

Mounting mode

Pendant

Shape and measurements

Length: 41.34 in
Width: 41.34 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 55.28 W

Protection

IP: 20
Designation labels: CE