Product data sheet

SRT-SYSTEM IP20-SRGV 1XCAMU/95 40°(SPOT) LED - GERÄTETRÄGER FUNKTIONSMODUL VARIABEL MIRO-SILVER® R… 4200 930 (SPOT) DALI2 VW RAL 9016 REFLECTOR (SRT+19105606220_37801010130_30GRAD)


REGIOLUX



IP 20 IK 03 CE

SRT-Quick-fit mounting system, LED device mount variable function module spotlight camu, Modullänge/375. Gear tray made of a galvanised, profiled steel sheet; surface coated with polyester resin paint; with rotary catches for rapid fitting in the mounting rail, spotlight unit made of die-cast aluminium, powder-coated housing, 330° rotation and 90° swivel angle. Gear tray can be positioned variably on the mounting rail; Housing colour traffic white RAL 9016. Light distribution Wide–Beam by means of MIRO-SILVER® High gloss faceted reflector of aluminium. Suitable for VDU workstations, 65° < 3000 cd/m² omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a 0.7m connection cable for variable positioning of the device mount with a 5-pin, quick-fit plug connector in the light run and free phase pre-selection. Transparent safety glass panel, Exchange reflectors 20°,30° and 60° available as accessories They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 382mm x 55mm x 190mm Swivel and turn area (x/y/z): + 90° / 0° / 330° Beam angle: 40° (C0) Placement: LED, Colour rendering/Light colour CRI ≥ 90 / 3000K Colour tolerance: 2SDCM LED service life: 50000h L90/B10 (Tq 35°C) Nominal luminous flux: 4154lm Luminaire luminous efficiency: 131lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 32W Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (10°C bis 35°C) Ambient temperatur: ta 10°C to 35°C Special properties: Ready for IoT UGR lat./long.: max. 17.8 / 18.3 (40gradW) Certification mark: IP20, Protection class I, 65°<3000 cd/m², F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGV/0375 1xcamu /95 40° LED 4200 930 DALI2 vw RAL 9016 Article number: 19105606220 Product deep link: https://www.regiolux.de/en/article/19105606220 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	3000 K
Nominal lamp power	31.8 W	CRI	90
Total flux	4110 lm	LOR	100%
Luminous efficacy	129 lm/W	Total power	31.8 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Height: 4.53 in

Diameter: 3.74 in

Design

Color of housing: White

Electric

System power: 31.8 W

Appliance Class: 0

Protection

IP: 20

IK: 03

Designation labels: CE