


Product data sheet

CAP L35 C83 E3
CAPO LED EMERGENCY
DEXTRA




Capo LED - CAP L35 C83, 2735 luminaire lumens C83 LED decorative luminaire suitable for both ambient and accent lighting, matt grey aluminium spun rear housing, translucent grey center collar, opal refractor, supplied complete with 3m wire suspension kit. Optional extras: H - High Frequency Dimming (Analogue 1-10v) S - Switch Dimming (retractable wall switch) D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) RED- Red Collar ORA - Orange Collar GRN - Green Collar BLE - Blue Collar OP - Opal Collar

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	4 W	CRI	80
Total flux	407 lm	LOR	100%
Luminous efficacy	102 lm/W	ULOR	22%
		Total power	4 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	22.51 W	CRI	80
Total flux	2735 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	20%
		Total power	22.51 W

Mounting mode

Pendant

Shape and measurements

Height: 15.98 in

Diameter: 12.44 in

Adjustability

Height adjustable

Electric

System power: 26.51 W

Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Designation labels: CE