


Product data sheet

KOMBIC 70 SUT 1500 IP40 NW WFL D B/B
K71ST1540WF840DBB
LAMP



LAMP Suspended or ceiling mounting downlight KOMBIC 70 SUT 1500. Body made of recycled aluminium extrusion at a rate of 75% and reflector made of recycled polycarbonate R-PC FR WHITE TM non-brominated flame retardant additive. Flammability grade V0 according to UL94. Inner reflector finished in black and Wide Flood optic for greater efficiency and to achieve controlled light distribution and low glare level, less than UGR<16. Heatsink made of die-cast aluminium. COB LED, colour temperature 4000K and IRC80. Electronic DALI gear included. IP40 rated. Insulation Class II. Photobiological safety group 0. LED life time: 72.000 L80 B10. Available finishes: White and black.

Light output 1



1 x LED			
Nominal lamp power	10.3 W	LOR	100%
Lamp flux	911 lm	Total flux	909 lm
Luminous efficacy	88 lm/W	Total power	10.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Height: 5.51 in
Diameter: 2.76 in

Adjustability

Fixed

Electric

System power: 10.3 W
Appliance Class: II

Protection

IP: 04