
Product data sheet

LIQUID LINE LINEAR MODULES SUSPENDED - G3
QG3ASE-830H-L600
LIGHTNET



LED pendant light system. Direct-indirect or direct-only light distribution. Luminaire body made of aluminium profile with 60mm width. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. Arbitrary combination of 90° modules with all linear as well as curved elements of the Liquid Line 3D family is possible. Highly flexible system suited for millimetre accurate customizing as well as individual solutions. Each module is also available as stand-alone luminaire. End caps to be ordered separately. For continuous lines of light one connector and one cord-holder for each joint to be ordered separately.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	82
Total flux	1509 lm	LOR	100%
Luminous efficacy	79 lm/W	Total power	19 W

Mounting mode

Pendant

Shape and measurements

Length: 23.62 in
Width: 2.36 in
Height: 3.94 in

Adjustability

Height adjustable

Electric

System power: 19 W

Protection