Product data sheet


MEGA GÜRTELLINSE
611886.004
RZB



IP 65 IK 05

Series: MEGA GÜRTELLINSE Luminaire tube Ø 115 mm made of corrosion-resistant aluminium profile, powder coated. Recessed stainless steel mounting base. Non-corrosive gear compartment made of mould-cast dual compound thermoplastic with integral TP gasket. With membrane valve as a standard to avoid condensed water. Seawater-resistant coating. Mouth-blown luminaire glass, clear, drum lens shape. A light transmission bar made of highly transparent, clear plastic (PMMA) with lasered optical structure diverts the light horizontally, ensuring optimum and even light distribution on the floor. The robust stainless steel mounting base ensures long-term stability. Slotted holes in the base for easy subsequent and simple alignment of the luminaire. Connection box on base, max. 2 x 3 x 2.5 mm² for through wiring. Colour: silver, matt (approx. RAL 9006) Diameter: 140 mm Height: 750 mm Lamp: QA60 (clear) System power: 57 W Rated luminous flux: 520 lm Luminous efficiency: 9 lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP 65

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	57 W	Socket	E27
Lamp flux	915 lm	LOR	100%
Luminous efficacy	16 lm/W	ULOR	50%
CCT	3000 K	Total flux	915 lm
CRI	90	Total power	57 W

Mounting mode

Standing / Bollard, Pole integrated

Shape and measurements

Height: 29.53 in
Diameter: 5.51 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 57 W

Protection

IP: 65
IK: 05