Product data sheet

DAMP PROOF EMERGENCY 1200 32W 830 IP65 GY 4058075541368

LEDVANCE










Damp-proof luminaires, classic shape with integrated emergency lighting function. Product features: Luminaire suited for normal lighting and emergency lighting. Certified according to European norms (EN 60598-1:2015; EN 60598-2-22:2014). Self-contained luminaires. Emergency lighting function: battery discharge time of 3 h. Function test of emergency lighting: automatic (AT). Battery technology: LiFePO4. High luminous efficacy: up to 139 lm/W. Type of protection: IP65. Beam angle: 110°. Product benefits: Seamless integration of luminaires with emergency lighting function into general lighting. Easy wiring thanks to included prewired driver and battery for Emergency lighting function. Simple testing of luminaires with emergency lighting function thanks to integrated automatic test function. Convenient visualization of results of automatic test with an included control LED. Operation of integrated emergency lighting function with long life LiFePO4 battery with 3h battery discharge time. Uniform light distribution in normal operation. Energy savings of up to 60 % (compared to luminaires that use fluorescent lamps. Easy installation, no tools required for connection. 3 years guarantee. Areas of application: Emergency illumination of escape routes. Antipanic lighting. Buildings requiring up to 3 h emergency light operation. Industrial and storage facilities. Car parks and underpasses. Garages. Workshops, assembly lines. Equipment / Accessories: Stainless steel clamps with safety screws included. Mounting accessories included (suspension kit, theft protection kit).

Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	32 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	32 W

Mounting mode

Ceiling mounted, Pendant

Shape and measurements

Length: 47.24 in Width: 3.23 in Height: 2.68 in Weight: 1.46 kg

Adjustability

Fixed

Design

Material impression: Plastic Color of housing: Anthracite / graphite

Electric

System power: 32 W Appliance Class: I

Information regarding emergency functions

Emergency lighting only Emergency sign: N/A

Protection

IP: 65 IK: 08

Designation labels: CE

Other operating numbers

Ambient temperature range: 41...95°F