



Product data sheet

LIQUID LINE WAVE MODULES SURFACE - A3
QA30SE-830H-WVQ-R150-L2355
LIGHTNET




LED surface mounted light system. Direct only light distribution. Luminaire body made of aluminium profile with 60mm width. Surface white, silver, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen with optimized glare reduction especially for workplaces. Satin opal diffuser for general lighting. Driver integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial \leq MacAdam 3. Colour rendering CRI>80 or CRI>90. Arbitrary combination of all 90° modules, X- and Y-connectors, linear and curved elements of the Liquid Line 3D family is possible. Highly flexible system suited for millimetre accurate customizing as well as individual solutions. Each module is also available as stand-alone luminaire. End caps to be ordered separately.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	75 W	CRI	82
Total flux	4954 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	75 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	75 W	CRI	82
Total flux	4954 lm	LOR	100%
Luminous efficacy	66 lm/W	Total power	75 W

Mounting mode

Ceiling mounted

Electric

System power: 150 W

Shape and measurements

Length: 23.62 in

Width: 2.36 in

Height: 3.15 in

Protection

Adjustability

Height adjustable