



Product data sheet

RECESSED DIRECTIONAL SPOTLIGHT NOVO SQUARE SQUARE 10W 1000L
2005.7378 - NOVO SQR DS SB CR68 LED1000-930 L 35 SR ONF
REGENT



Recessed directional spotlight Novo Square inner ring set back, with LED, system power: 10 W, luminous flux of luminaire 1000 lm, colour rendering index CRI > 90, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, 300 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, silver, RAL 9006, with lens, 35°, operating unit included in delivery, ON/OFF, protection class II, ingress protection IP20 / IP44, glow wire test 650 °C, impact strength: IK 01 this product contains a light source of energy efficiency class E and EPREL registration number: 863701 L = 78 mm, B = 78 mm, ceiling cutout □ 68 mm up to 73 mm, ET = 99 mm swivelling 15°

Light output 1



1 x LED			
Nominal lamp power	10 W	LOR	100%
Lamp flux	1000 lm	Total flux	1004 lm
Luminous efficacy	100 lm/W	Total power	10 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.07 in
Width: 3.07 in
Height: 1.50 in
Weight: 0.824 kg

Adjustability

Rotatable, Tilttable

Design

Color of housing: Silver gray

Electric

System power: 10 W
Appliance Class: II

Protection

IP: 44
IK: 01