


Product data sheet

6409/4128-5103-162-1110-11-850011
267859
STAHL




Emergency luminaire With LED GRP Explosion-protected Type: 6409/4128-5103-162-1110-11-850011 Enclosure material: Polyester resin Translucent cover material: Polycarbonate Version: Standard Number of lamps: 1 Lamp wattage: 25 W Dimensions (L x W x H): 857 x 183,5 x 125 mm AC rated operational voltage: 110,00 - 240,00 V Application range (zones): 2 , 21, 22 Gas explosion protection: II 3 G Ex db ec IIC T4 Gc Dust explosion protection: II 2 D Ex tb op is IIIC T100 °C Db II 3 D Ex tc IIIC T100 °C Dc Min. ambient temperature: -30 °C Max. ambient temperature: +50 °C Through wiring: With 6 conductors 2.5 mm² Installed terminal strip: PE + N + L1 + L2 + L3 + L' Max. solid connect. terminals: 6,00 mm² Max. fine. strand. conn. term.: 4,00 mm² Battery capacity: 7 Ah Battery version: NiCd battery, gas-tight Emergency light operation: Continuous light Or stand-by light Operating time: 1.5 h em. lighting operation Battery operating voltage: 6 V Self-test function: With (standard) Drilled holes: 3 x M25 Accessories: Provided Screw connections: 2 x M25 Ø 7 – 17 mm Cable entry material: Polyamide, black Stopping plug: 2 x M25 x 1.5 Stopping plug material: Polyamide, black For further information, see: www.r-stahl.com WebCode 6409C

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	25 W	CRI	82
Total flux	2910 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	25 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	5000 K
Nominal lamp power	14.3 W	CRI	82
Total flux	1892 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	14.3 W

Mounting mode

Ceiling mounted, Pendant

Electric

System power: 39.3 W
Appliance Class: I

Shape and measurements

Length: 34.23 in

Width: 6.61 in

Height: 5.07 in

Adjustability

Fixed

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 66

IK: 08