Product data sheet


LIGHTING FOR ADMINISTRATIVE AND OFFICE BUILDINGS
V1-R3-00010-31OP0-2004550 GR070 2.0 588X588X50 MM IP40 45W 5000K OPAL
VARTON



IP 40 IK 03

LED luminaire solution for GRILIATO ceilings. Stainless steel housing with white powder coating. Application: administrative facilities For GRILIATO suspended ceilings with special rails. Can be fixed at the level of GRILIATO cells with a height of 30, 40 or 50 mm. Length, mm: 588 Width, mm: 588 Height/depth, mm: 50 Input voltage (AC, 50Hz), V: 176...264 Ingress protection (IP): IP40 Impact resistance: IK03 Protection class: I AC frequency, Hz: 50 Flicker, %: 2 Climatic modification and category of placement: УХЛ4 Power factor: 0,95 https://www.varton.ru/products/ofisnoe-osveshchenie/varton-dlya-grilyato-gr-seriya-2-0/gr070-2-0-588x588x50-mm-ip40/svetodiodnyy-svetilnik-varton-gr070-2-0-45-vt-5000-k-588kh588kh50-mm-s-plankami-dlya-podvesa-s-opalo_2/

Light output 1



1 x LED

Nominal lamp power	45 W	LOR	100%
Lamp flux	5760 lm	Total flux	5760 lm
Luminous efficacy	128 lm/W	Total power	45 W
CCT	5000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.15 in
Width: 23.15 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 45 W

Protection

IP: 40
IK: 03