


Product data sheet

SUPRALUM
251048.002.1
RZB



Series: Supralum Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: die-cast aluminium, powder-coated. Diffuser fastening: spring system. Diffuser: hand-blown opal glass, satin finish. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 280, H 100 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 810lm System power: 18W Beam Angle: 125° Unified Glare Ratio: 18,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	810 lm	LOR	100%
Luminous efficacy	45 lm/W	ULOR	26%
		Total power	18 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in

Diameter: 11.02 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 43

IK: 03