Product data sheet

REKTOR 1XLED GI 2700K MEDIUM BLACK STRUC-SMOKED BRONZE 12826067

MODULAR








Guiding the way around your space Rektor, the surface-mounted spotlight by Modular, will guide the way around your space. The unique feature of the Rektor is that all the technical workings are concealed within the fixture. The innovative tilting technology allows you to rotate the bulb holder through 360°, as well as adjusting it upwards or downwards through 90°. All without a single wire being visible. This makes it a perfect example of accent lighting. Its extensive adjustability and metal colour accent on the housing make it a genuine must-have. Rektor is also handy for highlighting a wall or specific object. Designed in cooperation with Couvreur-Devos.

Light output 1



I x LED	
Nominal lamp power	16.25 W
Lamp flux	1461 lm
Luminous efficacy	57 lm/W
CCT	2700 k
CRI	90

LOR	74%
Total flux	1085 lm
Total power	19 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 3.07 in Width: 9.72 in Height: 1.81 in Weight: 1.38 kg

Adjustability

Rotatable, Tiltable

Electric

System power: 19 W

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20