



Product data sheet

1989 MINI RODIO - POWER SWITCH - SYMMETRIC 4000K CRI 70 49W CLD GRAPHITE
414915-00
DISANO



Housing: in die-cast aluminium with cooling fins integrated in the cover. Optics: in high-performance PMMA resistant to high temperatures and UV rays. Diffuser: tempered glass, 4 mm thick, resistant to thermal shock and impact (UNI EN 12150-1:2001). Coating: the fully automated powder-coating cycle involves a polyester-based, salt-spray corrosion-resistant and UV-stabilised paint. Special coating: Upon request: protective coating recommended for marine environments within 5 km (3 miles) of the sea. Heat Sink: the heat sink is designed and made to allow the LEDs to operate at temperatures capable of ensuring excellent performance/output and long service life. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. Equipment: - with galvanised and painted bracket - cable for electrical connection - EN 61547 compliant surge protection - silicone rubber gasket - external screws and bolts in stainless steel.

Light output 1



1 x LED			
Nominal lamp power	49 W	LOR	100%
Lamp flux	8323 lm	Total flux	8322 lm
Luminous efficacy	170 lm/W	Total power	49 W
CCT	4000 K		
CRI	70		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 15.75 in

Width: 10.75 in

Height: 2.76 in

Adjustability

Fixed

Design

Material impression: Aluminum

Color of housing: Anthracite / graphite

Electric

System power: 49 W

Appliance Class: I

Protection

IP: 66

IK: 08

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...104°F