

Product data sheet


FLAT MOON 650 SUSPENSION UP-DOWN LED 4000K GI BLACK STRUC
13305132
MODULAR



IP
20

Enchanting moonlight Contemporary architectural projects love a minimalist, slim lighting design. Flat moon is a stylish, reduced height fixture (78 mm) that distributes a soft, yet functional light. Office-compliant when combined with one of the prismatic diffusers, it is also a perfect fit for public spaces, hotels, restaurants or retail environments. Exceptionally versatile, Flat moon can be either surface-mounted, recessed or suspended (with two types of suspension kits for either down or up/down lighter) and even directly mounted and connected onto the gear. It comes in three sizes: 450, 650 or 950 mm diameter.

Light output 1



| | | | |
|--------------------|----------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 85 W | LOR | 74% |
| Lamp flux | 11661 lm | ULOR | 23% |
| Luminous efficacy | 88 lm/W | Total flux | 8589 lm |
| CCT | 4000 K | Total power | 98 W |
| CRI | 90 | | |

Mounting mode

Pendant

Electric

System power: 98 W

Shape and measurements

Length: 25.59 in
Width: 25.59 in
Height: 3.07 in
Weight: 10.5 kg

Protection

IP: 20

Adjustability

Fixed