Product data sheet

RAX 200 U19 WHITE 27W 4000K RA>80 8246087834

SG ARMATUREN







Recessed LED downlight. Made of fire-resistant polycarbonate. SDCM 2. L90/B10>50,000, Supplied with 3000K/4000K LED. Complete with driver and quick connection between driver and downlight for super quick and simple mounting. Can be mounted to ceiling panels with a thickness of 1–50 mm. The luminaire comes complete with ceiling ring RAL9010 gloss 25 made of die-cast aluminium. Matt reflector. Light distribution: Direct Light technic LED 27W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class I IP20 Energy and approvals A++ CE Materials and finish Housing: Flame retardant polycarbonate Colour: White Optics: Aluminium Mounting/Connection Recessed (downlight), Indoor Max. luminaires per circuit breaker: B10: 21, B16: 34, C10: 35, C16: 58

Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
27 W	CRI
3210 lm	LOR
119 lm/W	Total power

Mounting mode

Ceiling recessed

Shape and measurements

Length: 8.78 in Width: 8.78 in Height: 6.58 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 27 W Appliance Class: I

Protection

IP: 20

4000 K 80 100%

27 W