Product data sheet


RAX SOFT 150 SATIN 2220LM 4000K RA>80 TRAILING EDGE DIMMING
7021982125089
SG ARMATUREN



IP 20 IK 08

Rax Soft 150 is a high-performance downlight for lighting in public buildings, offices, corridors etc with an excellent light control by a combination of optimized lens and reflector optics. Available with satin matt reflector for high efficiency. Rax Soft 150 is installed easily with springs that fit ceiling panels with a thickness of 1–50 mm. Light distribution Direct Light technic LED 18W 4000K Ra>80 SDCM 2 L90/B10 >100,000 hrs Optic Satin Matt Reflector Control/Dimming Trailing edge dimming Protection Class II SELV IP20 IK08 Energy and approvals CE Materials and finish Housing: Flame retardant polycarbonate Colour: Satin matt Optics: PMMA Polymethylmethacrylat Mounting/Connection Recessed (downlight), Indoor Cable 3x0,75mm² Quick connector Max. luminaires per circuit breaker: B10: 25, B16: 41, C10: 40, C16: 65

Light output 1



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2220 lm	Total flux	2221 lm
Luminous efficacy	123 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.54 in
Width: 6.54 in
Height: 3.27 in

Adjustability

Fixed

Electric

System power: 18 W
Appliance Class: II

Protection

IP: 20
IK: 08