Product data sheet


FLAT CRYSTAL
211420.002.1
RZB



IP 43 IK 02

Series: Flat Crystal Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic. Diffuser fastening: spring system. Diffuser: opal glass, silk finish, with crystal border. IP43 ceiling mounted, IP44 wall mounted. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 370, H 118 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 1200lm System power: 13W Beam Angle: 117° Number of fittings B10A: 136 Number of fittings B16A: 218 Number of fittings C10A: 136 Number of fittings C16A: 218 Inrush current: 0,15A Unified Glare Ratio: 18,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1200 lm	LOR	100%
Luminous efficacy	92 lm/W	ULOR	15%
		Total power	13 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.65 in
Diameter: 14.57 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 13 W

Protection

IP: 43
IK: 02