

# Product data sheet

MEGA GÜRTELLINSE  
611882.0031  
RZB




IP  
65

IK  
02

Series: MEGA GÜRTELLINSE Classic bollard with innovative housing design and high-quality LED optics. Luminaire tube Ø 115x160mm made of corrosion-resistant aluminium profile, powder coated. Recessed stainless steel fixing plate. Non-corrosive gear compartment made of mould-cast dual compound thermoplastic with integral TP gasket. With membrane valve as a standard to avoid condensed water. Seawater resistant coating. Mouth-blown luminaire glass, clear, drum lens shape. A light transmission bar made of highly transparent, clear plastic (PMMA) with lasered optical structure diverts the light horizontally, ensuring optimum and even light distribution on the floor. The robust stainless steel mounting base ensures long-term stability. Elongated holes in the base for subsequent and simple alignment of the luminaire. Driver integrated. Connection box on base, max. 2x3x2.5 mm<sup>2</sup> for through wiring. Colour: anthracite metallic (DB703) Diameter: 140x160mm Height: 500x160mm Lamp: LED System power: 10x160W Rated luminous flux: 490x160lm Luminous efficiency: 49x160lm/W Control gear: Regulated power supply Protection class: I Type of protection: IPx16065

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10 W	CRI	80
Total flux	490 lm	LOR	100%
Luminous efficacy	49 lm/W	ULOR	54%
		Total power	10 W

## Mounting mode

Standing / Bollard, Pole integrated

## Shape and measurements

Height: 19.69 in  
Diameter: 5.51 in

## Adjustability

Fixed

## Electric

System power: 10 W

## Protection

IP: 65  
IK: 02