


Product data sheet

SILVANA
366100
FLOS



• Outdoor luminaire for installation on ceiling. • Configuration: die-cast aluminium fixing base and frames, EN AB47100 alloy (low copper content). Extruded aluminium body. • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered transparent glass and silicone gasket

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	26 W	Socket	G24Q-2
Lamp flux	1800 lm	LOR	21%
Luminous efficacy	15 lm/W	Total flux	386 lm
CCT	3000 K	Total power	26 W
CRI	84		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 5.91 in

Width: 5.91 in

Height: 11.42 in

Adjustability

Fixed

Electric

System power: 26 W

Appliance Class: I

Protection

IP: 65

IK: 08