Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0079.05

LEIPZIGER LEUCHTEN









For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL - or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour	lamp
Naminal lamp nawar	50 V

Nominal lamp power	50 W	LOR	85%
Lamp flux	3500 lm	ULOR	28%
Luminous efficacy	48 lm/W	Total flux	2962 lm
CCT	2000 K	Total power	62 W
CRI	25		



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	85%
Lamp flux	5600 lm	ULOR	28%
Luminous efficacy	57 lm/W	Total flux	4739 lm
CCT	2000 K	Total power	83 W
CRI	25		

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

System power: 62-83 W

Protection

IP: 55