Product data sheet


LIGHT LINEAR PT 3 STREET AND AREA LUMINAIRES
LI-21173-LC-T4-W40
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 100 km/h - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	81.8 W	CRI	80
Total flux	8446 lm	LOR	100%
Luminous efficacy	103 lm/W	ULOR	100%
		Total power	81.8 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 39.37 in
Width: 5.91 in
Height: 3.54 in
Weight: 29.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 81.8 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C