


Product data sheet

POWERSVISION 4 SURFACE HIGH BAY LUMINAIRES
PW49-GP214-ME-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Extruded aluminium pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	209 W	CRI	80
Total flux	24909 lm	LOR	100%
Luminous efficacy	119 lm/W	Total power	209 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 32.20 in
Width: 11.22 in
Height: 11.81 in
Weight: 17.8 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 209 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 07
Surface temperature: 40°C