

Product data sheet

TERRA EDELSTAHL 245
641302.000.1
RZB




IP
68

IK
10

Series: TERRA EDELSTAHL 245 In-ground luminaire for pedestrian areas. Housing made of corrosion-resistant die-cast aluminium, powder-coated. Marine grade stainless steel square shaped cover and screws. Flush mounted toughened glass. High performance LED refractor optics. Beam angle can be adjusted up to 10°;degrees from vertical. Integral flexible power cord H07-RN8F. Use of in-ground support is necessary, please order chosen version for your application separately. Colour: stainless steel Length: 245;mm Width: 245;mm Height: 28;mm Lamp: LED System power: 26;W Rated luminous flux: 2350;lm Luminous efficiency: 90;lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP;68

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26 W	CRI	80
Total flux	2350 lm	LOR	100%
Luminous efficacy	90 lm/W	ULOR	100%
		Total power	26 W

Mounting mode

Floor recessed

Electric

System power: 26 W

Shape and measurements

Length: 9.65 in
Width: 9.65 in
Height: 0.08 in

Protection

IP: 68
IK: 10

Adjustability

Fixed