Product data sheet

ROBERT III (1-ARMED BEADED) 9.863.2032.06


LEIPZIGER LEUCHTEN





Mounting height 4,50 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in color - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack -Available in any RAL or DB colour without surcharge - scope of supply includes hot galvanized and painted offset pole, dia. 102 mm, and bracket

Light output 1



I x High pressure sodium v	vapour iamp
Nominal lamp power	70 W
Laman flux	E600 lm

Lamp flux 5600 lm
Luminous efficacy 54 lm/W
CCT 2000 K
CRI 25

LOR 80%
Total flux 4493 lm
Total power 83 W

Mounting mode

Pole integrated, Ceiling mounted

Shape and measurements

Height: 11.81 in Diameter: 23.62 in

Design

Material impression: Matt Color of housing: White

Electric

System power: 83 W Ballast: ECG

Protection

Designation labels: CE

Other operating numbers

Ambient temperature range: -13...95°F