

Product data sheet

DEECOS P MINI
911479.003.76
RZB




IP
20

IK
06

Series: Deecos Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Ceiling canopy made of powder-coated sheet steel with magnetic attachment. Transparent pendant cable 2000 mm, can be shortened, with integrated steel cable. Housing: powder coated die cast aluminium. Heat-resistant plastic ring. Lens made of plastic (polycarbonate) included, can be changed without tools. Lamp (LED) included. LED converter included. Available Colours: deep black, matt (RAL 9005) Type of Installation: Pendant Dimensions: D 87, H 195 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK06 (1 Joule) Luminaire flux LED: 2450lm System power: 29W Beam Angle: 44° Number of fittings B10A: 21 Number of fittings B16A: 34 Number of fittings C10A: 35 Number of fittings C16A: 57 Inrush current: 18A Unified Glare Ratio: 17,3 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	30 W	CRI	80
Total flux	2350 lm	LOR	100%
Luminous efficacy	78 lm/W	Total power	30 W

Mounting mode

Wall mounted

Shape and measurements

Height: 7.68 in
Diameter: 3.43 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 30 W

Protection

IP: 20
IK: 06